## **AMENDMENT TO THE CLAIMS**

Claims 1-32. (canceled)

Claim 33. (new) A system for fastening at least two panels together, said system comprising:

at least one pair of oppositely disposed retaining profiles arranged at the edges of a first panel, and at least one pair of oppositely disposed retaining profiles arranged at the edges of a second panel, wherein mutually oppositely disposed retaining profiles on said first panel complement each other such that said second panel, having similar retaining profiles, can be fastened to said first panel;

said oppositely disposed retaining profiles having complementary hook elements that can be hooked one into the other, said complementary hook elements comprising:

a first hook projection connected to the panel by a first leg on an upper portion of the edge of said panel, said first hook projection having an inclined retaining surface, such that said first hook projection is reduced from its free end towards the first leg; and

a second hook projection connected to the panel by a second leg on a lower portion of the edge of said panel, said second hook projection having an inclined retaining surface, such that said second hook projection is reduced from its free end towards the second leg, wherein

in an assembled condition the inclined retaining surface of the hook projection on said first panel bears against the retaining surface of the complementary hook projection of the second panel to hold said panels against each other so as to afford a gap-free floor surface; and

the hook projection connected to the panel by the leg on the lower portion of the edge of the first panel bears against the leg connected to the panel at the upper portion of the second panel; and

a space is provided between the hook projection connected to the panel by the leg on the upper portion of the edge of the second panel and the leg connected to the panel at the lower portion of the first panel.

Claim 34. (new) The fastening system according to claim 33 wherein a first retaining profile of the at least one pair of oppositely disposed retaining profiles, comprises:

a first hook element formed from the first leg, said first leg projecting approximately perpendicularly from the edge of the panel and which is arranged at the upper portion of the edge of the panel, and wherein

said first hook projection faces towards the underside of the panel, and a second retaining profile of the at least one pair of oppositely disposed retaining profiles, which is opposite the first retaining profile, comprises:

a second hook element formed from the second leg, said second leg projecting approximately perpendicularly from the opposite edge of the panel and which is arranged at the lower portion of the edge of the panel, and wherein

said second hook projection faces towards the top side of the panel.

Claim 35. (new) The fastening system according to claim 33 wherein the retaining surfaces of the hook projections engage each other such that complementary hook projections can be hooked one into the other only by elastic deformation.

Claim 36. (new) The fastening system according to claim 35 wherein a clearance is provided between the end of the hook projection at the lower portion of the second panel and the edge of the first panel and the end of the hook projection at the upper portion of the first panel in the assembled condition bears against the second panel at least in the region of the upper portion of the edge of the second panel.

Claim 37. (new) The fastening system according to claim 33 wherein intermediate spaces provided with clearance in the assembled condition of two panels form adhesive pockets.

Claim 38. (new) The fastening system according to claim 33 wherein the panels substantially comprise an MDF, HDF, or chipboard material.

Claim 39. (new) A system for fastening at least two panels together, said system comprising:

at least one pair of oppositely disposed retaining profiles arranged at the edges of a first panel, and at least one pair of oppositely disposed retaining profiles arranged at the edges of a second panel, wherein mutually oppositely disposed retaining profiles on said first panel complement each other such that said second panel, having similar retaining profiles, can be fastened to said first panel;

said oppositely disposed retaining profiles having complementary hook elements that can be hooked one into the other, said complementary hook elements comprising:

a first hook projection connected to the panel by a first leg on an upper portion of the edge of said panel, said first hook projection having an inclined retaining surface, such that said first hook projection is reduced from its free end towards the first leg; and

a second hook projection connected to the panel by a second leg on a lower portion of the edge of said panel, said second hook projection having an inclined retaining surface, such that said second hook projection is reduced from its free end towards the second leg, wherein

in an assembled condition the retaining surface of the hook projection on said first panel bears against the retaining surface of the complementary hook projection of the second panel to hold said panels against each other so as to afford a gap-free floor surface; and

the hook projection connected to the panel by the leg on the upper portion of the edge of the first panel bears against the leg connected to the panel at the lower portion of the second panel; and

a space is provided between the hook projection connected to the panel by the leg on the lower portion of the edge of the second panel and the leg connected to the panel at the upper portion of the first panel.

Claim 40. (new) The fastening system according to claim 39 wherein a first retaining profile of the at least one pair of oppositely disposed retaining profiles, comprises:

a first hook element formed from the first leg, said first leg projecting approximately perpendicularly from the edge of the panel and which is arranged at the upper portion of the edge of the panel, and wherein

said first hook projection faces towards the underside of the panel, and
a second retaining profile of the at least one pair of oppositely disposed retaining profiles, which
is opposite the first retaining profile, comprises:

a second hook element formed from the second leg, said second leg projecting approximately perpendicularly from the opposite edge of the panel and which is arranged at the lower portion of the edge of the panel, and wherein

said second hook projection faces towards the top side of the panel.

Claim 41. (new) The fastening system according to claim 39 wherein the retaining surfaces of the hook projections engage each other such that complementary hook projections can be hooked one into the other only by elastic deformation.

Claim 42. (new) The fastening system according to claim 41 wherein a clearance is provided between the end of the hook projection at the lower portion of the second panel and the edge of the first panel and the end of the hook projection at the upper portion of the first panel in the assembled condition bears against the second panel at least in the region of the upper portion of the edge of the second panel.

Claim 43. (new) The fastening system according to claim 39 wherein intermediate spaces provided with clearance in the assembled condition of two panels form adhesive pockets.

Patent and Trademark Office Application Serial No. 10/019,195 Page 12

Claim 44. (new) The fastening system according to claim 39 wherein the panels substantially comprise an MDF, HDF, or chipboard material.